

MULTIPURPOSE

HIGH SHOE

HIGH SHOES

S3

SRC

## The +

- Great value
- Full grain leather cowhide leather
- Retro-reflective stripe with multiple faces
- Double density injected PU sole
- Defined heel



### DESCRIPTION

AGATE II is an ankle safety shoe. Its full grain upper brings a better resistance and breathability than split leather whereas the ankle padding provides supports to the wearer. The polyester mesh lining improves breathability and hence comfort. The out & mid-soles are made of injected polyurethane of different density which balance comfort and durability. This shoe features a steel toe-cap and plate for protection against puncture and fall of heavy objects. The retro-reflective band with patterns improves safety of wearers while in dark environments. AGATE II is equipped with a cleated outsole with good adhesion properties. Ideal for indoor as well as outdoor works.

### SECTORS

Service

Second work

Infrastructure, building industry

Transport and logistics

### SOLD PACKAGING

REF.	EU	US	
9AGH010034	34	2.5	10
9AGH010035	35	3	10
9AGH010036	36	4	10
9AGH010037	37	4.5	10
9AGH010038	38	5.5	10
9AGH010039	39	6	10
9AGH010040	40	7	10
9AGH010041	41	8	10
9AGH010042	42	8.5	10
9AGH010043	43	9.5	10
9AGH010044	44	10	10
9AGH010045	45	11	10
9AGH010046	46	11.5	10
9AGH010047	47	12.5	10
9AGH010048	48	13.5	10
9AGH010049	49	14	10

See also

Variant



9AGL010

## TECHNICAL FEATURES

<b>Sub-family</b>	High shoe	<b>Color</b>	Black
<b>Rod</b>	Full grain leather cowhide leather	<b>Clean sole</b>	Removable, textile and foam
<b>Loops</b>	Metal eyelets	<b>Midsole</b>	Injected polyurethane
<b>Wearing sole</b>	Double density polyurethane	<b>Main assembly</b>	Injected assembly
<b>Lining</b>	Moisture wicking non-woven lining	<b>Weight</b>	606 g per shoe in size 9
<b>Closure</b>	Lacing	<b>Anti perforation sole</b>	Stainless less
<b>Toe cap</b>	Steel	<b>Reflective trim</b>	Retro-reflective stripe with multiple faces at the back
<b>Heel</b>	Defined	<b>Reinforced part of shoe</b>	None
<b>Work environment</b>	Multipurpose	<b>Examples of applications</b>	Luggage handler, delivery driver, ...

## INSTRUCTIONS FOR USE AND STORAGE

### Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

### Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

### Washing instructions :

- Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## LEGISLATION

EN ISO 20345:2011

**S3 SRC**

**S1P** : Closed heel, antistatic shoe, fuel and oil resistant contact outsole, puncture resistant midsole, resistant to a 1100 Newtons, water penetration and absorption resistant upper, spiked outsole, puncture resistant midsole,  
**SRC** : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. II

Major risks

Retailer stamp