

ALFAGOMMA INDUSTRIAL INDUSTRIAL HOSE DIVISION ALFAGOMMA GROUP		TECHNICAL DATA SHEET		DATE: 04/12/19	
PETROL PUMP code: 6K5AA					
					
APPLICATION:		GASOLINE AND DIESEL FUEL DISPENSING AND TRANSFER			
TUBE:		BLACK CONDUCTIVE NBR			
REINFORCEMENT:		HIGH TENSILE TEXTILE BRAID – AS WIRES			
COVER:		BLACK CONDUCTIVE CR – ABRASION, OZONE, HYDROCARBON AND FIRE RESISTANT			
WORKING TEMPERATURE:		-30°C +55°C (-22°F +131°F)			
SAFETY FACTOR:		3:1			
NORMS:		EN 1360/1: 2013 grade Ω			
TECHNICAL DATA					
INSIDE DIAMETER, mm:		16	19	25	
OUTSIDE DIAMETER, mm		26	29	36	
MINIMUM BEND RADIUS, mm:		80	100	150	
NOMINAL WEIGHT, kg/m:		0.370	0.440	0.640	
MAXIMUM WORKING PRESSURE, bar:		16	16	16	
ELECTRICAL RESISTANCE, Ω/length		<10⁶	<10⁶	<10⁶	

ALFAGOMMA INDUSTRIAL S.p.A.

Cap. Soc. € 1.872.000,00 I.V. – REA Teramo N° 92225 – C. F. e P.IVA N° IT 00730430675

 Registered Office, Administration and Plant/Sede legale, Amministrativa e Stabilimento: Nucleo Industriale – 64020 S. Atto (TE) ITALY – TEL. +39 0861.44.21 – FAX +39 0861.58.85.70
 Sales/Commerciale: Via Torri Bianche, 1 – 20059 Vimercate (MI) ITALY - TEL. +39 039.60.16.1 – FAX +39 039.62.87.279

www.alfagomma.com e-mail: info@alfagomma.it