

EVAC**PC**

DIGITAL MATRIX	1
-----------------------	----------

- LED power meter
- 13 system fault LEDs
- Two fault state buttons
- Two emergency state buttons
- Six EMG zone status LED pairs
- Six EMG zone select buttons
- Six BGM zone select LEDs
- Six BGM zone select buttons
- Six BGM zone volume control knobs
- Two BGM source status LEDs
- Three knobs for BGM volume, treble, and bass levels
- All-call button
- Indicator test button
- EMG state button
- Alert message button
- EN- 54certified

PC

MUSIC SOURCE	1
---------------------	----------

- MP3 PLAYBACK FROM SD CARD AND USB INPUTS
- FM TUNER WITH RDS, PRESETS AND DIGITAL CONTROL
- SIMULTANEOUS OPERATION OF SD/USB PLAYER AND FM TUNER
- SEPARATE OUTPUTS FOR DIGITAL SOURCE AND FM TUNER

PC

POWER AMPLIFIER	3
------------------------	----------

- 480 W power amplifier in a 3U high 19" housing
- EN 54-16 certified and EN 60849 compliant
- 70 V / 100 V and 8 ohm outputs
- Dual inputs with priority switching
- 100 V input for slave operation on 100 V speaker line
- EN -54certified

PC

BATTERY CHARGER	1
------------------------	----------

- 12 A battery charger
- 6x 40 A, 3x 5 A outputs
- 150 A back-up current
- Fully supervised, EN 54-4 certified
- Under-voltage and over-voltage protection
- EN -54certified

PC

CALL STATION	1
---------------------	----------

- Stylish six-zone call station
- Six zone selection keys, all-call key and momentary PTT-key for calls
- Selectable gain, speech filter, limiter, and output

level for improved intelligibility

- LED indications for zone selection, fault, and emergency state
- Call station extension provides seven additional zone and zone group keys
- EN- 54certified

PC

CEILING SPEAKER	167
------------------------	------------

- 6 W ceiling loudspeaker, suitable for 100 V connection with power tapping of: 6, 3, 1.5 and 0.75 Watt.
- The optional back-box LC3-CBB fully protects the loudspeaker from dust and dripping water from above,
- The loudspeaker frame, grill and back-box are manufactured from self-extinguishing ABS according to UL 94V0.
- EN- 54certified

PC

RACK FOR EVAC	1
----------------------	----------

- **Steel thickness** 2mm for mounting profile, 1.2mm for the rest
- **Static load** up to 800KG
- **Protection class** IP20
- **Door** Perforated Front and back doors
- **Side Panels** Removeable From Outside with Lock
- **Fan hole** 4 Fans with thermostat included
- **Status** Flat Pack

MT

FIRE RESISTANCE CABLE	7000
------------------------------	-------------

- FIRE RESISTANCE CABLE
- 120MIN RESISTANCE
-
-
-
-
-
-
-