	Lotkini - GULF						
n/n		Name	Technical description	Unit	Quantity	Unit cost, \$	Cost, \$
1		Frieze	Building The frieze of the building, 600 mm high, with a polymer coating. Complete with substructures. Installation of panels without visible fasteners.	м2	14.52		
2	i alt Store	3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (English) the front panel is made of 3rm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters.	piece	9.00		
3	15-2047-15 - Lotto Providi	3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (Georgian) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters.	piece	9.00		
4		Profile	The profile of the junction of the frieze to the building in the upper part with a polymer coating (orange), $h=200 \text{mm}$	м2	4.84		
5		Parapet	Parapet 700 mm wide made of galvanized steel 0.5 mm thick. Without an internal metal frame. Fabrication at a construction site.	м2	16.94		
6	77	Mood lightning	Strobe with LED illumination for illumination of the frieze of the building. Made of trapezoidal plastic profile with LED lighting.	м	24.20		
	Total:						0.00
7		Frieze	Hasec The frieze of the canopy is made of rolled panels, with a polymer coating, h=900 mm. Complete with a subsystem for attaching to metal structures of the canopy and hardware. The possibility of service is provided. All hardware with an open mount is painted in the color of the panels.	м2	27.81		0.00
8	sl	Frieze	Canopy frieze corner, 900mm high, made of welded aluminum in blue color. Substructures are made of galvanized steel profiles. Mounting system without hardware and fasteners on the front surface.	piece	4.00		0.00
9	(Êru Li	3D letter (sign)	Molded inset letters "Gulf" (English) with a front surface of 3mm thick acrylic glass. Internal LED backlight. (2 set of letters of 4 pieces)	piece	8.00		0.00
10	6.4231	3D letter (sign)	Molded inset letters "Guff" (Georgian) with a 3 mm thick acrylic glass front surface. Internal LED backlight. (4 sets of letters of 5 pieces each)	piece	8.00		0.00
11		Mood lightning	Profile with LED Businession in compound Billing is is noted of extraded alumnum. Profile synthesis costing, and an extra structure of the structure of extra structure of the canopy. Complete with hardware.	М	31.00		0.00
12		Ceiling	Suspended ceiling made of galvanized steel 0.7mm thick consisting of: white panel 325 mm wide, RT docking profile, metal frame made of galvanized pipe and fittings, hardware.	м2	107.00		0.00
13		LED lightning	The LED lamp is built into the suspended ceiling. Rectangular. For external use. The degree of protection is IP65. The body is cast aluminum. The luminous flux is 10600t, the cool remperature is 5000K. Power consumption - no more than 100 watts. Operating temperature - 30+50. Easy removable design for maintenance and replacement.	piece	6.00		0.00
14		Parapet	The parapet is made of galvanized steel 0.5 mm thick, with locks. Without an internal metal frame. Made on the construction site.	м2	21.63		0.00
15		Profile	Transition profile of the frieze abutting to the canopy ceiling $h$ = 0.4 m with polymer coating (white).	м2	31.00		0.00
16		Pillar cladding	The covering of the canopy support is conventionally nectangular in cross- section, make of galvanized steel with paymer coating. Complete with a section, make of galvanized steel with paymer coating. Complete with a log support is divergent by the batter well frame of the canopy. The height of the size of the core of the support. Height 4.7m , 2pc	м2	18.80		
17		Pillar cladding	The covering of the cancpy support of square / rectangular cross-section, made of galvarized steel with polymer coating. Near the building. Complete with a subsystem for starticing the skin to the metal frame of the cancey. The height of the start of the core of the support height of the cancey, the sweep depends on the size of the core of the support.	м2	4.80		0.00
18		Information box	The information cantilever double-sided box. The box plates are made of molded plastic with a seal or applique, complete with a metal trame. With internal illumination by LEDs along the contour.	ШТ	2.00		
19		Totem	The price stable is 5500 mm tor 5 types of hist "two-string Single-support. The sender of the stable is 0500 mm tor 5 types and the 1.1 mm that development of the string benchmark of polymer coaling. The singl "SOLET" is a light molecule invoces it consists of when- mic scriptic gives and the U-priving. The transaction is made by whet EDs. The absorbs point and the optimization is made by the LEDs. The absorbs point mode of aluminum with a polymer coaling with an internal development of the string of the strin	ΨT	1.00		
20	<u> </u>	Protective arc steel	Protective arc for installation in front of/on the safety islands.	шт	2.00		0.00
21		Trash bin	Combined service unit on a fuel platform made of polymer coated steel. Includes a tower holder, a washing station for washing glasses, a box for gloves and a garbage container.	ШТ	1.00		0.00
	TOTAL :	I	l		Cost of mater	ial without VAT	0.00
				Tran	sportation cor Installation co	nst without VAT	0.00
					. 5141 00		0.00

Lotkini - GULF