

MDB														
Circuit Breaker	Power	Power	Power	Current, Amp			Voltage	Circuit Breaker						Customer
	Pn	DF		L1	L2	L3			Lenght m	Cable Type	IN Cores, mm2	Voltage Drop		Description
#	kW		kW									Type	U	
Q1	200.00	0.80	160.00	271.19			400	MCCB 400A	380	NA2XH	2X(4X150)	8.6	2.14	LVDB
QM1	50.00	0.80	40.00	67.8	67.8	67.8	380	MCCB 100A	15	N2XH-J	5X35	1.0	0.25	DB-1
QM2	50.00	0.80	40.00	67.8	67.8	67.8	380	MCCB 100A	85	N2XH-J	5X35	5.4	1.43	DB-2
QM3	16.00	0.80	12.80	21.7	21.7	21.7	380	MCB 32A	35	N2XH-J	5X6	3.9	1.03	VRF-1
QM4	16.00	0.80	12.80	21.7	21.7	21.7	380	MCB 32A	50	N2XH-J	5X6	5.6	1.47	VRF-2
QM5	16.00	0.80	12.80	21.7	21.7	21.7	380	MCB 32A	50	N2XH-J	5X6	5.6	1.47	VRF-3
QM6	16.00	0.80	12.80	21.7	21.7	21.7	380	MCB 32A	50	N2XH-J	5X6	5.6	1.47	VRF-4
QM7	7.00	0.80	5.60	9.5	9.5	9.5	380	MCB 20A	60	N2XH-J	5X4	4.4	1.15	AHU-1
QM8	9.00	0.80	7.20	12.2	12.2	12.2	380	MCB 20A	70	N2XH-J	5X4	6.6	1.73	H.C-1
QM9	7.00	0.80	5.60	9.5	9.5	9.5	380	MCB 40A	30	N2XH-J	5X6	1.4	0.38	LIFT
QM10	0.20	0.80	0.16	0.3			20	MCB 16A	80	N2XH-J	3X2.5	0.0	0.23	V-1