

Position		Name	Technical description	Unit	Quantity	Unit cost, \$	Cost, \$
Store frieze							
1		Frieze	The frieze of the GULF STORE, 600 mm high, made of aluminum flat panels with polymer coating. Complete with substructures. Installation of panels without visible fasteners.	m2	45.75		
2		3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (English) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters. Logotype and illumination must be completed according to IP 66 standard .	piece	9.00		
3		3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (Georgian) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters. Logotype and illumination must be completed according to IP 66 standard .	piece	9.00		
		Alucobond (GRAY)	White sheathing of the walls of the building with alucobond 4mm flat panels. Complete with a subsystem for attaching to building structures and hardware. Complete with galvanized steel . Insulation between wall and alucobond must be completed with 10mm rockwool . Installation of the facade system without visible fasteners.	m2	69.34		
		Alucobond (WHITE)	White sheathing of the walls of the building with alucobond 4mm flat panels. Complete with a subsystem for attaching to building structures and hardware, made by galvanized steel . Insulation between wall and alucobond must be completed with 10mm rockwool . Installation of the facade system without visible fasteners.	m2	146.08		
4		Escarpments	Sheathing of window and door openings on the building is made of 4 mm thick alucobond with a polymer coating . The special design of slopes with the use of alucobond extrusion profiles ensures the absence on the front surfaces . The window (door) slope is volumetric . Fastened by means of the P-A08 profile , which ensures the absence of hardware on the front surfaces .	m2	58.24		
		Mood Lighting	Strobe with LED illumination for for illumination of the frieze of the building made of trapezoidal plastic profile with LED lighting	M	15.40		
5		Parapet	Parapet 700 mm wide made of galvanized steel 0.5 mm thick . Without an internal metal frame. Fabrication at a construction site.	m3	22.40		
Total:							0.00
Building							
1		Frieze	The frieze of the canopy is made of aluminum flat panels, with a polymer coating, h=1000 mm. The orange and blue waves made of 4MM acrylic molded panels with internal LED backlight , waves and illumination construction completed according to IP 66 standard . Complete with a subsystem for attaching to metal structures of the canopy and hardware made by galvanized steel . The possibility of service is provided. All hardware with an open mount is painted in the color of the panels.	m2	88.00		
		3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (Georgian) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 7 letters. Logotype and illumination must be completed according to IP 66 standard .	piece	7.00		
		3D letter (sign)	Molded letters "BUSINESS" embedded in the frieze of the building (English) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 8 letters. Logotype and illumination must be completed according to IP 66 standard .	piece	8.00		
		Mood Lighting	Strobe with LED illumination for for illumination of the frieze of the building made of trapezoidal plastic profile with LED lighting	M	88.00		
		Profile	Transition profile of the frieze abutting to the Building ceiling W = 0.32 m with polymer coating (white).	m2	28.16		
2		3D letter (sign)	3D sign on the facade of the Building " . Made of molded acrylic with UV printing and applique. With internal LED lighting . English sign. Signand illumination elements must be completed according to IP66 standard. DIAMETER = 1.4 M	piece	1.00		
2		3D letter (sign)	3D sign on the facade of the Building " . Made of molded acrylic with UV printing and applique. With internal LED lighting . English sign. Signand illumination elements must be completed according to IP66 standard. DIAMETER = 2.8 M	piece	1.00		
6		Parapet	The parapet is made of galvanized steel 0.5 mm thick, with locks. Without an internal metal frame. Made on the construction site.	m2	61.60		
Total:							0.00
Transportation:							0.00
Installation:							0.00
Total cost							0.00