





















GULF+ SENAKI

Position		Name	Technical description	Unit	Quantity	Unit cost, \$	Cost, \$
Building							
1		Frieze	The frieze of the building, three-part, is made of rolled blue panels and flat blue, orange and white panels, 670 mm high, with a polymer coating, 1.8 mm aluminum. Complete with substructures. Installation of panels without visible fasteners.	m2	14.07		
		Frieze	Welded building frieze element 670 mm high "Gulf Wave". Made from rolled welded blue panels and flat blue and orange panels, 1.8mm aluminum with polymer coating. The supporting structures are made of galvanized steel profiles and frames. Fastening system without hardware and fastenings on the front surface.	m2	2.68		
2		3D letter (sign)	Molded letters "Gulf Store" (ENGLISH) inset into the frieze of the building. With a molded front part made of PMMA Plexiglas 3mm with film adhesive before molding. Internal LED lighting with white LEDs. Set of 9 letters. H=145-260mm. The logo and lighting must be made according to the IP 66 standard.	piece	9.00		
3		3D letter (sign)	Molded letters "Gulf Store" (Georgian) inset into the frieze of the building. With a molded front part made of PMMA Plexiglas 3mm with film adhesive before molding. Internal LED lighting with white LEDs. Set of 9 letters. H=145-260mm. The logo and lighting must be made according to the IP 66 standard.	piece	9.00		
		3D letter (sign)	Molded letters "Office" (English) inset into the frieze of the building. With a molded front part made of PMMA Plexiglas 3mm with film adhesive before molding. Internal LED lighting with white LEDs. H=160-265mm	piece	6.00		
		3D letter (sign)	Molded letters "Office" (Georgian language) inset into the frieze of the building. With a molded front part made of PMMA Plexiglas 3mm with film adhesive before molding. Internal LED lighting with white LEDs. H=160-265mm	piece	5.00		
		Mood lightning	Profile with LED backlight. Designed to organize illumination of the frieze along the perimeter of the building. The organization of backlighting is made using an extruded aluminum profile with built-in white LED boards of cold and warm glow, followed by filling with a compound. Profile painting color - RAL 5002 (gloss). Complete with hardware.	M	20.00		
		Mood lightning	Profile with LED backlight. Designed to organize illumination of the frieze along the perimeter of the building. The organization of backlighting is made using an extruded aluminum Mic profile with built-in white LED cold-glow boards, followed by filling with a compound. Profile painting color - RAL 5003. Complete with hardware.	M	25.00		
		Building wall cladding	Sheathing of the walls of the building with alucobond 4mm flat panels. Complete with a subsystem for attaching to building structures and hardware, made by galvanized steel. Insulation between wall and alucobond must be completed with 10mm rockwool. Installation of the facade system without visible fasteners.	m2	82.14		
		Escarpments	Sheathing of window and door openings on the building is made of 1.8 mm thick aluminum with a polymer coating. The special design of slopes with the use of aluminum extrusion profiles ensures the absence of hardware on the front surfaces. The window (door) slope is volumetric. Fastened by means of the P-408 profile, which ensures the absence of hardware on the front surfaces.	m2	20.24		
4		Parapet	Parapet 930 mm wide made of galvanized steel 0.5 mm thick. Without an internal metal frame. Fabrication at a construction site.	m3	23.25		
Total:						8.00	
Canopy 22.4 M							
7		Frieze	The frieze of the canopy is three-part, made of rolled dark blue panels and flat light blue and orange panels with polymer coating. Aluminum 1.8 mm. H of frieze panels = 1000 mm. The frieze is supplied complete with a subsystem for fastening to canopy metal structures and hardware. The possibility of service is provided. All hardware, when fastened open, is painted in the color of the panels.	m2	13.40		
8		Frieze	Canopy frieze corner - 900mm high, made of flat welded aluminum in blue and white colours with waves. Substructures are made of galvanized steel profiles. Mounting system without hardware and fasteners on the front surface.	piece	9.00		
9		3D letter (sign)	Molded inset letters "Gulf+" (ENGLISH) with a 3 mm thick acrylic glass Plexiglas front surface. Internal LED backlight: (1 sets of letters of 6 pieces each) Logotype and illumination must be completed according to IP 66 standard. H=435-480mm.	piece	1.00		
10		3D letter (sign)	Molded inset letters "გულფ+" (Georgian) with a 3 mm thick acrylic glass Plexiglas front surface. Internal LED backlight: (1 sets of letters of 5 pieces each) Logotype and illumination must be completed according to IP 66 standard. H=435-480mm.	piece	1.00		
		3D letter (sign)	3D sign on the facade of the canopy "Gulf" (English). Made of molded acrylic with UV printing and applique. With internal LED lighting. English sign,sign and illumination elements must be completed according to IP66 standard. H=1430*1530mm.	piece	1.00		
		3D letter (sign)	3D sign on the facade of the canopy ". Made of molded acrylic with UV printing and applique. With internal LED lighting. Georgian sign,sign and illumination elements must be completed according to IP66 standard. H=1430*1530mm.	piece	2.00		
		Mood lightning	Profile with LED backlight. Designed to organize illumination of the frieze along the perimeter of the canopy. The organization of backlighting is made using an extruded aluminum profile with built-in white LED boards of cold and warm glow, followed by filling with a compound. Profile painting color - RAL 5002 (gloss). Complete with hardware. 2 strips.	M	22.40		
12		Ceiling	Suspended ceiling made of galvanized steel 0.7mm thick consisting of: white panel 325 mm wide, RT docking profile, metal frame made of galvanized pipe and fittings, hardware.	m2	102.00		
13		LED lightning	The LED lamp is built into the suspended ceiling. Rectangular. For external use. The degree of protection is IP66. The body is cast aluminum. The luminous flux is 10600lm, the color temperature is 5000K. Power consumption - no more than 100 watts. Operating temperature - 30...+50. Easy removable design for maintenance and replacement.	piece	6.00		
14		Parapet	The parapet is made of galvanized steel 0.5 mm thick, with locks. Without an internal metal frame. Made on the construction site.	m2	15.70		
		Profile	Transition profile of the frieze abutting to the canopy ceiling h = 0.3 m with polymer coating (white).	m2	6.72		
16		Pillar cladding	The covering of the canopy support of square / rectangular cross-section, made of galvanized steel with polymer coating. Near the building. Complete with a subsystem for attaching the skin to the metal frame of the pillar. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 4.5m, 2pc	m2	21.60		

		Pillar cladding	The covering of the canopy support of square / rectangular cross-section, made of galvanized steel with polymer coating. Near the building. Complete with a subsystem for attaching the skin to the metal frame of the pillar. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 1.m , zpc	m2	4.80		
17		Information box	Double-sided console information box, without backlight. The console is covered with panels made of TsAM 1 - 0.7 mm with a polymer coating in RAL 9003 color. The brand element "Gulf Wave" is glued to the panel in the form of an applique film ORAJET 3640 - 010 with solvent printing of a color image. 1200/650mm	piece	2.00		
18		Totem	*The price steel is 7000 mm for 4 types of fuel.Two-string. Single-support. The panels of the steel under the logo are made of 1.8 mm thick aluminum with a polymer coating. The sign "GULF" is a light molded invoice. It consists of white-milk acrylic glass with UP-printing. The internal LED-illumination is made by white light-emitting diodes, the counter-illumination is made by blue LEDs. The advertising panel is made of aluminum with a polymer coating with an internal LED backlight. The price panel is made of tempered FLAT glass with a thickness of 4 mm. The price lines are made in a polymer-coated housing, illuminated with white LEDs. The types of fuel are made in the form of a replaceable plate made of silicate tempered glass with an application. The illumination of the plates is made by white-glow LEDs. The side light profile is made of bent plastic with yellow-glow LEDs. Support for the steel: welded metal frame, round section. The frame elements undergo shot blasting, stripping, followed by degreasing of the surface, and additional treatment of the welds with an anticorrosive primer containing zinc. Anticorrosive protection of structures is carried out by applying a zinc-containing epoxy primer, with a layer thickness of 75-150 microns and a two-layer polyurethane enamel. The steel is equipped with an IR remote control of price lines. With a mortgage. Pice sign and illumination elements must be completed according to IP66 standard.	piece	1.00		
19		Protective arc steel	Protective arc for installation in front of/on the safety islands.	piece	2.00		
20		Trash bin	Combined service unit on a fuel platform made of polymer coated steel. Includes a towel holder, a washing station for washing glasses, a box for gloves and a garbage container.	piece	1.00		
<b>Total:</b>						<b>0.00</b>	
						<b>0.00</b>	
						<b>0.00</b>	
						<b>0.00</b>	